



RTAPE GRAPHIC TAPES

The NEW, universal clear application tape for maximum versatility & precision

Clear Choice® is an ultra-clear, application tape that provides exceptional performance and versatility for the widest range of sign applications.

AT60n Low Tack

A Low Tack film for transferring large cut graphics and protecting digital prints.

AT65 High Tack

Universal high tack film for transferring small and fine detail cut graphics and vinyl films with tight release liners.

AT75.1 High Tack

Embossed surface film ideal for small to medium size cut graphics, with air-egress micro channels for bubble-free lamination of tape to film.

New! Product Improvements

- Enhanced Adhesion
- Improved release liner adhesion with Conform characteristics
- Improvements to lifting and transferring graphics
- No adhesive residue with wet applications
- No water whitening upon contact with water/solution

Applications

- Textured and matte finish vinyl films
- Fine lettering
- Textured wrap, window and wall films
- Thermal die cuts

Product Information

- Clear film
- Repositionable
- Easy handling and removal
- No milky residue and water whitening when used for wet applications

AT60n and AT65

- Emboss/Finish: Fine Texture for easy release/unwind and installation

AT75.1

- Emboss/Finish: Heavy Surface Texture with Air Egress Micro tunnels

AT75.1 vs AT60n ▼ See the difference!



Printed on Digital Coated 80# cover on a Ricoh C751EX

TECHNICAL DATA ▶

Physical Properties

Color Transparent
Shelf Life 1 year

	AT60n	AT65	AT75.1
Color	Transparent	Transparent	Transparent
Adhesive	Acrylic	Acrylic	Modified polyacrylate
Caliper	Embossed Polypropylene	Embossed Polypropylene	Embossed HOPE
	3.7 mil (93 μ)	3.7 mil (93.7 μ)	4.25 mil (106.4 μ)
Tack Level	Low	High	High
Adhesion to Steel*	1-4 N/100 mm (1-3 oz.)	2.1-6.5 N/100 mm (2 - 6 oz.)	2.1 N/25 mm (7.5 oz.)
Die-Cut Graphics Size	Large	Small-Med	Small-Med
Wet Application Installation	Good	Excellent	Excellent
Compatible Vinyl	Gloss/Smooth	Gloss/Smooth	Gloss/Smooth and Matte/Textured Vinyl
Tensile	25 MPa (3600 psi)	25 MPa (3600 psi)	13 MPa (2000 psi)
Elongation	750%	750%	300-500%

* TEST METHOD: PSTC-101

WARRANTY Tapes are only warranted to be free of defects in workmanship or materials at time of shipment. Nekoosa will replace or credit any material deemed to be defective. No acceptance or responsibility for loss, damage, or expense, implied or otherwise, shall be assumed by the seller or manufacturer. The end user assumes all risk and liability.