



# POLI-TACK 870 Universal

## Product Information

Transparent Polyester film coated with a cross-linked acrylic adhesive offering excellent temperature resistance, ageing and UV stability.

The adhesive can be removed without residue even after long periods of usage.

POLI-TACK 870 Universal transfer film is suitable for thermal transfer of heat sealing substrates, i.e. for the transfer of Flex-film onto textiles.

## Technical Data

<b>Carrier:</b>	PET-film, transparent	
<b>Adhesive:</b>	Acrylic	
<b>Adhesion [N/cm]:</b>	0,50	+/- 10 %
<b>Thickness [mm]:</b>	0,12	+/- 5 %
<b>Liner:</b>	Siliconised PP film, white	

## Dimensions

500 mm x 25 m  
500 mm x 40 m  
750 mm x 25 m\*  
750 mm x 40 m\*  
1.524 mm x 25 m\*  
1.524 mm x 40 m\*

\* Non-standard dimension. Converted after order entry. Extended delivery times may occur

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

**POLI-TAPE Klebefolien GmbH**  
Zeppelinstraße 17  
53424 Remagen – GERMANY

Phone: +49 2642 – 98 36 0  
Fax: +49 2642 – 98 36 37

E-Mail: [info@poli-tape.de](mailto:info@poli-tape.de)  
Internet: [www.poli-tape.de](http://www.poli-tape.de)

11/06/2019

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.