

# POLI-TAPE

HEAT TRANSFER VINYL

## POLI-FLEX® PREMIUM

POLI-FLEX® STRETCH **S**

POLI-FLEX® BLOCKOUT SOFT **B**



STANDARD	<b>B S</b>	401 WHITE	461 BABY PINK	464 SAPPHIRE	<b>NEW</b>	692 MINT	METALLIC	<b>B</b>	420 GOLD METALLIC
		417 BEIGE	460 MAGENTA	<b>S</b>	406 ROYAL BLUE	416 BROWN		<b>B</b>	430 SILVER METALLIC
	<b>NEW</b>	694 PASTEL YELLOW	462 FUCHSIA	405 NAVY BLUE	470 ANTIQUE GOLD	484 ANTIQUE SILVER			
	419 LEMON YELLOW	472 CARDINAL RED	474 LIGHT GREEN	412 GREY	403 NEON BLUE				
	418 MEDIUM YELLOW	409 BORDEAUX	467 APPLE GREEN	693 LIGHT GREY	440 NEON YELLOW				
	<b>B S</b>	410 YELLOW	471 AUBERGINE	<b>S</b>	404 GREEN	441 NEON GREEN			
	<b>B</b>	415 ORANGE	414 PURPLE	468 AQUA GREEN	402 BLACK	442 NEON ORANGE			
	473 FLAME RED	475 ICE BLUE	413 TURQUOISE	4290 GLOSSY WHITE	4291 GLOSSY BLACK	<b>NEW</b>		690 NEON RED	
	<b>B S</b>	408 RED	465 SKY BLUE	469 MILITARY GREEN	4292 GLOSSY RED	<b>B</b>		443 NEON PINK	
	476 VIOLET	466 LILAC	407 FOREST GREEN	4293 GLOSSY GOLD	<b>NEW</b>	691 NEON BERRY			



160°C  
130°C BLOCKOUT SOFT



15 SEC  
5 SEC BLOCKOUT SOFT



2,5 - 3,0 BAR



WARM  
LUKE WARM



80°C  
TUMBLE DRY  
DRY CLEANING



MULTI LAYER



OEKO-TEX®  
CONFIDENCE IN TEXTILES  
STANDARD 100  
14.0.44284 HOHENSTEIN HTTI  
Tested for harmful substances.  
www.oeko-tex.com/standard100



500 MM X 25 M  
500 MM X 10 M  
1000 MM X 25 M  
1524 MM X 25 M

Please find detailed information in the technical data sheets | Detaillierte Informationen entnehmen Sie den technischen Datenblättern

**#BeCreative**

POLI-FLEX® TURBO  
POLI-FLEX® PREMIUM  
POLI-FLEX® PEARL GLITTER  
TUBITHERM® FLOCK  
POLI-FLEX® IMAGE  
POLI-FLEX® BLOCKOUT SOFT  
POLI-FLEX® NYLON  
POLI-FLEX® SPORT  
POLI-FLEX® STRETCH  
POLI-FLEX® PRINTABLE  
TURBO PRINT  
ULTIMATE PRINT



YouTube



**HEAT TRANSFER VINYLs 4 every challenge**

**TURBO PRINT 4036 MATT** is the printable polyurethane transfer vinyl equipped with the same special hotmelt and features like POLI-FLEX® TURBO

**TURBO PRINT 4036 MATT** ist die bedruckbare Polyurethan Transferfolie mit dem selben speziellen Heißschmelzkleber und Eigenschaften wie POLI-FLEX® TURBO

130°C  
5 SEC